

# RX-Series

LED-backlit Display 24" | 22"

## Raise the Bar for Security




With its specialised gamma selection and black-level adjustment, the enhanced RX-Series renders images of the highest quality even under unfavourable lighting conditions. The series is built to last and perform in 24/7 security and surveillance environments. Its durability is enhanced by AG Neovo's Anti-Burn-in™ technology, which prevents ghosting while performing nonstop mission-critical operations; NeoV™ Optical Glass and metal casing shield it from scratches or other damages.





### Enhanced Gamma Selection


Selectable gamma curves visually optimise different kinds of images. The AG Neovo specialised image settings enhance colour, brightness, sharpness and contrast ratio, allowing the RX-Series to improve the light, shadows and colour balance of videos.



Others



AG Neovo RX-Series



### Flexible Integration


The RX-Series is equipped with VGA, DVI, HDMI & DisplayPort 1.2 inputs for analogue and digital signal support respectively. It also has composite (BNC) inputs/ outputs for video looping of surveillance cameras signals and DVRs.

### Flicker-Free Backlight

The flicker-free backlight of the RX-Series ensures a comfortable viewing experience by reducing eye strain after long periods of use.



Others



AG Neovo RX-Series

### Features

- Anti-Burn-in™ technology
- NeoV™ Optical Glass
- Gamma selection for image clarity even under critical sources
- 3D Comb Filter/ Deinterlace/ Noise Reduction/ Freeze
- EcoSmart Sensor detects ambient lighting conditions and automatically adjusts the brightness levels
- Adjustable VGA/DVI input settings for analogue images
- Versatile inputs: VGA, DVI, Composite (BNC), HDMI, S-Video, DisplayPort & RS232
- Flicker-free backlight for eye comfort
- Durable metal casing
- Rigorous screening of the components for mission-critical 24/7 applications

- Selectable aspect ratio and zoom function for ultimate image size
- Quick signal-switching time
- Composite (BNC x 2) & Audio passive looping
- Available in black and white
- Front-sided IP22 rating protects screens from liquid splash and dust
- Black-level adjustment for presenting the delicate detail of darkness
- Built-in speakers (2W x 2)



## Specifications

### RX-24E

### RX-22E

<b>Panel</b>	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD (VA Technology) 23.6" FHD 1920 x 1080 0.272 mm 250 cd/m <sup>2</sup> 20,000,000:1 (DCR) 178°/178° 16.7M 5 ms	LED-Backlit TFT LCD (VA Technology) 21.5" FHD 1920 x 1080 0.248 mm 250 cd/m <sup>2</sup> 20,000,000:1 (DCR) 178°/178° 16.7M 5 ms
<b>Horizontal Resolution</b>	TV Lines	620 TVL (NTSC) 625 TVL (PAL)	620 TVL (NTSC) 625 TVL (PAL)
<b>Frequency (H/V)</b>	H Freq. V Freq.	24 kHz-83 kHz 50 Hz-75 Hz	24 kHz-83 kHz 50 Hz-75 Hz
<b>Input</b>	DisplayPort HDMI DVI VGA Composite S-Video	x 1 1.4 x 1 24-Pin DVI-D x 1 15-Pin D-Sub x 1 BNC x 2 4-Pin mini DIN x 1	x 1 1.4 x 1 24-Pin DVI-D x 1 15-Pin D-Sub x 1 BNC x 2 4-Pin mini DIN x 1
<b>Output</b>	Composite	BNC x 2	BNC x 2
<b>External Control</b>	RS232 In	2.5 mm Phone Jack	2.5 mm Phone Jack
<b>Other Connectivity</b>	USB	2.0 x 1 (Service Port)	2.0 x 1 (Service Port)
<b>Audio</b>	Audio In  Audio Out Internal Speakers	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (RCA) Stereo Audio Jack (RCA) 2W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (RCA) Stereo Audio Jack (RCA) 2W x 2
<b>Power</b>	Power Supply Power Requirements On Mode Stand-by Mode Off Mode	External DC 12V, 2.7A 17W (On) < 0.5W < 0.5W	External DC 12V, 2.5A 16W (On) < 0.5W < 0.5W
<b>NeoV™ Optical Glass</b>	Thickness Reflection Rate Transmission Rate Hardness	3.0 mm (0.12") < 1% > 97% > 9H	3.0 mm (0.12") < 1% > 97% > 9H
<b>Operating Conditions</b>	Temperature Humidity	0°C-40°C (32°F-104°F) 10%-90% (non-condensing)	0°C-40°C (32°F-104°F) 10%-90% (non-condensing)
<b>Storage Conditions</b>	Temperature Humidity	-20°C to 60°C (-4°F-140°F) 5%-95% (non-condensing)	-20°C-60°C (-4°F-140°F) 5%-95% (non-condensing)
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)
<b>Stand</b>	Tilt	0° to 15°	0° to 15°
<b>Security</b>	Kensington Security Slot	Yes	Yes
<b>Dimensions</b>	w/Base (W x H x D) Packaging (W x H x D)	562.4 x 396.8 x 155.0 mm (22.1" x 15.6" x 6.1") 662.0 x 511.0 x 210.0 mm (26.0" x 20.1" x 8.3")	513.2 x 368.5 x 155.0 mm (20.2" x 14.5" x 6.1") 615.0 x 483.0 x 210.0 mm (24.2" x 19.1" x 8.3")
<b>Weight</b>	w/Base Packaging	7.9 kg (17.4 lb) 9.9 kg (21.8 lb)	6.8 kg (15.0 lb) 8.8 kg (19.4 lb)
<b>Regulation Approval</b>	Certification & Compliance	FCC, CB, CE, BSMI, RoHS, WEEE, REACH	FCC, CCC, CB, CE, BSMI, RoHS, WEEE, REACH
<b>Accessories</b>	Supplied	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
<b>Optional Accessories</b>		Wall Mount: PMK-01 Desk Mount: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mount (Landscape only): WMA-01 Wall Mount (Landscape only): WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mount: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mount (Landscape only): WMA-01 Wall Mount (Landscape only): WMK-01, WMK-03

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Stoevring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[displays.agneovo.com](https://displays.agneovo.com)